ThinkPad A475 Platform Specifications

Processor	AMD PRO A-Se	eries A	PUs						Dimensions	WxDxH: 13.25" x 9.15" x 0.79"; 336.6mm x 232.5mm x 19.95mm						
	Processor	# of	# of	Base	Max Turbo	Cache	Memory	Processor	Weight	Models		3-cell or 3 +			cell or 3 + 6-cell	
	Number	Cores	Threads	Frequency	Frequency	Odono	Types	Graphics		Magnesium	7	3.49 lb / 1.5			.92 lb / 1.78 kg	
	PRO A10-8730B			2.4 GHz	3.3 GHz			AMD Radeon™	0	PPS		3.63 lb / 1.6	65 kg	4.	.35 lb / 1.85 kg	
	PRO A12-8830B PRO A10-9700B PRO A12-9800B		4	2.4 0112	0.0 0112	2MB	DDR4-1866	R5 Graphics	Case color Case material	Black Display cover: Magnesium Hybrid or PPS (Magnesium Hybrid for US only);						
		4		2.5 GHz	3.4 GHz					Bottom: Glass-Fiber Reinforced Plastic						
				2.5 GHz	3.4 GHz			Radeon	Smart card reade	er Optional: Smart card reader						
				2.7 GHz	3.6 GHz			R7 Graphics	Media reader	4-in-1 reader (MMC, SD, SDHC, SDXC), supports SD 3.0, UHS-I						
	* Windows 7 is only supported by PRO A10-8730B and PRO A12-8830B								Ports	Three USB 3.1 Gen 1 (USB 3.0, one Always On), USB 3.1 Type-C Gen 2 (with the function of Power Delivery and DisplayPort).						
Graphics	AMD Radeon F							HDMI 1.4b, Ethernet (RJ-45), Dock connector								
	supports external digital monitor via HDMI or USB Type-C; supports three independent displays;									* Depending on many factors, actual data transfer speed may be lower than theoretical speed						
	Max resolution:			Type-C); 4	160@30Hz	(HDMI)	Monitor cable		Optional: Lenovo USB-C to VGA Adapter							
Chipset	AMD SoC (Syst	tem or	Chip) p	latform						HD720p resolution, fixed focus HD Audio, Realtek ALC3268 codec / stereo speakers, 2W x 2 /						
Memory	32GB max / 18	2GB max / 1866MHz DDR4, dual-channel capable, two DDR4 SO-DIMM sockets								dual array microphone, combo audio/microphone jack						
Display	Some: 14.0" (3				klight,		Keyboard	6-row, spill-resistant, multimedia Fn keys, optional LED backlight								
	220 nits Some: 14.0" (3		atio, 350:1		acklight IE	98	UltraNav™	TrackPoint	t® pointir	ng device and buttonless Mylar surface multi-touch touchpad						
	250 nits	aspect	atio, 700:1	contrast ra	° viewing a	ngle	Security	Power-on password, hard disk password, supervisor password, security keyhole								
Multi-touch (opt)	On-cell touch, supports 10-finger gesture (FHD only, US only)								Security chip	dTPM 1.2: discrete TPM 1.2, TCG Certified dTPM 2.0: discrete TPM 2.0. TCG Certified						
Storage	System has one I						Fingerprint reade									
	Some: HDD / SATA 6.0Gb/s, 2.5" wide, 7mm high, Active Protection System™ Some: SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high (e.g. xxxGB SSD) Some: M.2 SSD / PCIe NVMe, PCIe 3.0 x 2, 16Gb/s * Installed M.2 SSD is PCIe 3.0 x 4 but run at PCIe 3.0 x 2 due to M.2 SSD adapter limitation								NFČ	None						
									Internal battery External battery Max battery life	Optional: Integrated Li-Polymer 3-cell (24Wh)						
Ontical										Li-Polymer 3-cell (24Wh) or Li-ion 6-cell (48Wh)						
Optical	None	111ED	V O:	A FAIL AND A					(MobileMark® 2014)	Models	u life	3-cell 5.13 hr	3 + 3-4		6-cell 48Wh 10.26 hr	3 + 6-cell 48Wh 15.4 hr
Ethernet	Realtek® RTL81		9						,	* Max battery life 5.13 hr 10.26 hr 10.26 hr 15.4 hr * Battery life varies significantly with settings, usage, & other factors						
WLAN Bluetooth™	Realtek RTL882 Bluetooth 4.1 w								AC adapter	45W or 65W slim tip AC adapter, 45W or 65W USB Type-C AC adapter						
WWAN (optional)	One of the following	figurable	by model:		·		Operating system	One of the following, configurable by model:								
, , ,	 Wireless WAN 						 Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 10 Pro 64 									
	 Integrated Mo Qualcomm® S 			17455)				Windows 10 Home 64								
	* For non-WWAN	the model is	NOT WWAN	able			Windows 10 Pro 64									
SIM card (opt)	Micro-SIM card	pt Verizo	on LTE (US) SIM card			Limited warranty	One of the following, configurable by model:								
										1-year depot repair service3-year/1-yr battery depot repair service						
								3-year/1-yr battery limited onsite service								
								Mil-Spec test	MIL-STD-810G military testing							
									Environment	EPEAT™ Gold (US only); ENERGY STAR® 6.1; RoHS-compliant						
											10	- · · · · j /, = · · · =			,	

Note: The specifications above may not be available in all regions.